

Mator moyi RAVENOL WIV II 0W-30

CleanSynto®

Yopishqoqlik: 0W-30

To'liq sintetik



1 L

Mahsulot kodi:

1111101-001

Mahsulot kodi:

1111101-001-01-999

Shtrix-kod:

4014835718418



4 L

Mahsulot kodi:

1111101-004

Mahsulot kodi:

1111101-004-01-999

Shtrix-kod:

4014835718494



5 L

Mahsulot kodi:

1111101-005

Mahsulot kodi:

1111101-005-01-999

Shtrix-kod:

4014835718456



10 L

Mahsulot kodi:

1111101-010

Mahsulot kodi:

1111101-010-01-999

Shtrix-kod:

4014835718449



20 L

Mahsulot kodi:

1111101-020



20 L, ecobox

Mahsulot kodi:

1111101-B20



60 L

Mahsulot kodi:

1111101-060



60 L, bosilgan barrel

Mahsulot kodi:

1111101-D60

Mahsulot kodi:

1111101-D60-01-888

Shtrix-kod:

4014835718432



208 L

Mahsulot kodi:
1111101-208
Mahsulot kodi:
1111101-208-01-999
Shtrix-kod:
4014835718487



208 L, bosilgan barrel

Mahsulot kodi:
1111101-D28



1 000 L

Mahsulot kodi:
1111101-700

RAVENOL WIV II 0W-30 – to'liq sintetik, yuqori oqimlilikka ega motor moyi bo'lib, CleanSynto® texnologiyasidan foydalangan holda ishlab chiqarilgan. VW va Audi (2000-yildan boshlab ishlab chiqarilgan, WIV tizimi bilan jihozlangan) benzinli va dizel dvigatellari uchun mo'ljallangan. Shuningdek, eksklyuziv nasos-forsunka tizimiga ega avtomobillarga mos keladi.

Treniye va eskirishni kamaytiradi, yonilg'i sarfini tejaydi, natijada zararli moddalarning atmosferaga chiqarilishini kamaytiradi. Ajoyib past harorat xususiyatlariga ega. Avtomobil ishlab chiqaruvchi talablariga muvofiq uzoq muddatli moy almashtirish intervallarini ta'minlaydi.

RAVENOL WIV II 0W-30 barcha uzoq muddatli moy almashtirish intervallarini talab qiluvchi avtomobillarda ishlatilishi mumkin (VW 503 01 talab qiladigan modellar bundan mustasno).

RAVENOL WIV II 0W-30 quyidagi afzalliklarni ta'minlaydi:

- Volkswagen konserniga tegishli benzinli va dizel dvigatellarida ishonchli ishlash, shu jumladan nasos-forsunka (Pumpe-Düse-Motoren) tizimiga ega oxirgi avlod dizel dvigatellarida
- Past ishqalanish koeffitsienti
- Juda past haroratlarda dvigatelning muammosiz ishga tushishi
- Yuqori eskirishdan himoya va dvigatelning maksimal tozaligi, yonilg'i sarfini kamaytirish bilan birga
- Longlife xususiyatlari tufayli uzoq moy almashtirish intervali
- Atmosferaga chiqariladigan chiqindilarni kamaytirish orqali atrof-muhitni muhofaza qilish

Xususiyatlari

Ism	Ma'nosi	Audit
ACEA	A5, B5	
Talablarga mos keladi	VW 503.00, VW 506.00, VW 506.01	
Zichlik 20°C da	843 g/cm ³	EN ISO 12185
Rang	Jigarrang	ingl
Viskozite 100°C da	10.1 mm ² /s	DIN 51562-1
Viskozite 40°C da	55.3 mm ² /s	DIN 51562-1
Viskozite indeksi VI	174	DIN ISO 2909
Yuqori haroratli viskozite (HTHS) 150°C da	2.92 mPa*s	ASTM D5481
Past haroratli viskozite (CCS) - 35°C da	5351 mPa*s	ASTM D5293
Past haroratda nasoslanish viskozitesi (MRV) -40°C da	14.130 mPa*s	ASTM D4684
Qotish harorati	-45 °C	DIN ISO 3016
NOACK bug'lanishi	10.3 %	ASTM D5800
Yong'in chiqish harorati	220 °C	DIN EN ISO 2592
Ishqoriy son	10.2 mgKOH/g	ASTM D2896
Sulfatli kul miqdori	1.12 %wt.	DIN 51575
Tavsiyalar	VW 503 00, VW 506 00, VW 506 01	

OEM analoglari

BMW

83122219739

Volkswagen Group

GS60183M2, G052183S0, GR52183M2, G055183M2, G052183M2, GS60183M2EUR, GS60183M3, GS60183M3EUR, G052183M4, GR52183M4, G052183M6, GR52183M6, G052183M9

To'xtatilgan qadoqlash

Qadoqlash	Mahsulot kodi	Shtrix-kod
1 L	1111101-001-01-100 1111101-001-06-999	4014835101111 2200000021892
4 L	1111101-004-01-A01	

<i>Qadoqlash</i>	<i>Mahsulot kodi</i>	<i>Shtrix-kod</i>
5 L	1111101-005-01-100	4014835101159
	1111101-005-01-A01	2200000037060
		2200000041838
10 L	1111101-010-01-999	
20 L	1111101-020-01-999	
20 L, ecobox	1111101-B20-01-888	
60 L, bosilgan barrel	1111101-060-01-000	2200000038135
60 L	1111101-060-01-888	
	1111101-060-01-999	