

Mator moyi RAVENOL ALS 0W-30

USVO®
Ultra Strong Viscosity Oil

CleanSynto®

Yopishqoqlik: 0W-30

To'liq sintetik



1 L

Mahsulot kodi:

1111137-001

Mahsulot kodi:

1111137-001-01-999

Shtrix-kod:

4014835797710



4 L

Mahsulot kodi:

1111137-004

Mahsulot kodi:

1111137-004-01-999

Shtrix-kod:

4014835797796



5 L

Mahsulot kodi:

1111137-005

Mahsulot kodi:

1111137-005-01-999

Shtrix-kod:

4014835797758



10 L

Mahsulot kodi:

1111137-010

Mahsulot kodi:

1111137-010-01-999

Shtrix-kod:

4014835797741



20 L

Mahsulot kodi:

1111137-020

Mahsulot kodi:

1111137-020-01-999

Shtrix-kod:

4014835797727



20 L, ecobox

Mahsulot kodi:

1111137-B20



60 L, bosilgan barrel

Mahsulot kodi:

1111137-D60

Mahsulot kodi:

1111137-D60-01-888

Shtrix-kod:

4014835797734



208 L

Mahsulot kodi:

1111137-208

Mahsulot kodi:

1111137-208-01-999

Shtrix-kod:

4014835797789



208 L, bosilgan barrel

Mahsulot kodi:

1111137-D28

Mahsulot kodi:

1111137-D28-01-888

Shtrix-kod:

4014835797703



1 000 L

Mahsulot kodi:

1111137-700

RAVENOL ALS 0W-30 – to'liq sintetik, oson oqadigan motor moyi bo'lib, CleanSynto® texnologiyasi asosida ishlab chiqarilgan. Benzin va dizel dvigatelli yengil avtomobillar hamda kichik tonnajli tijorat transporti uchun mo'ljallangan. Qurilma tarkibida sazhe filtri va 3 komponentli katalizator TCW mavjud bo'lib, min. HTHS 3,5 mPa*s talablariga javob beradi.

RAVENOL ALS 0W-30 maxsus qo'shimchalar kompleksi tufayli sazhe filtri va uch komponentli katalizator TCW xizmat muddatini uzaytiradi.

Mazkur motor moyi yuqori viskozite indeksiga ega bo'lib, maxsus ishlab chiqilgan formulasi va yuqori sifatli asosiy moyi tufayli yuqori samaradorlikni ta'minlaydi. Sovuq ishga tushirishda a'lo darajadagi xususiyatlarga ega va optimal moylashni ta'minlaydi.

RAVENOL ALS 0W-30 yoqilg'i sarfini kamaytiradi, benzin va dizel dvigatelli yengil avtomobillar hamda kichik tonnajli tijorat transporti uchun uzoq muddatli almashtirish oralig'ida qo'llaniladi. Sazhe filtri va 3 komponentli katalizator TCW xizmat muddatini uzaytiradi. Maxsus formulasi tufayli **RAVENOL ALS 0W-30** aksariyat OEM ishlab chiqaruvchilari talablariga javob beradi.

RAVENOL ALS 0W-30 quyidagilarni ta'minlaydi:

- O'rtacha va yuqori yuklamalar ostida yoqilg'i tejash
- A'lo darajadagi eskirishdan himoya va yuqori tezlikda haydashda yuqori viskozite koeffitsienti, dvigatelning uzoq xizmat muddati
- -30 °C dan past haroratlarda ham sovuq ishga tushirishda mukammal natijalar
- Yuqori ish haroratlarida mustahkam moy plyonkasi
- Past bug'lanish darajasi, kamaytirilgan moy sarfi
- Yonish kamerasida, porshen halqalari va klapanlar hududida cho'kindi hosil bo'lmisligi
- Muhrlash materiallariga neytral ta'sir
- Uzoq almashtirish oralig'i (dvigatel ishlab chiqaruvchisi boshqacha belgilamagan bo'lsa)

Xususiyatlari

Ism	Ma'nosi	Audit
ACEA	C3	
Talablarga mos keladi	BMW Longlife-04, Chrysler MS-11106, MB 229.51	
Mos keladi	Honda, Mazda, Nissan, Suzuki, Toyota	
Zichlik 20°C da	841 g/cm ³	EN ISO 12185
Rang	Sariq-jigarrang	ingl
Viskozite 100°C da	12.1 mm ² /s	DIN 51562-1
Viskozite 40°C da	63.5 mm ² /s	DIN 51562-1
Viskozite indeksi VI	192	DIN ISO 2909
Yuqori haroratli viskozite (HTHS) 150°C da	3.65 mPa*s	ASTM D5481
Past haroratli viskozite (CCS) - 35°C da	5472 mPa*s	ASTM D5293
Past haroratda nasoslanish viskozitesi (MRV) -40°C da	15.400 mPa*s	ASTM D4684
Qotish harorati	-60 °C	DIN ISO 3016
NOACK bug'lanishi	9 %	ASTM D5800
Yong'in chiqish harorati	230 °C	DIN EN ISO 2592
Ishqoriy son	7.9 mgKOH/g	ASTM D2896
Sulfatli kul miqdori	0.78 %wt.	DIN 51575
Tavsiyalar	BMW Longlife-04, Chrysler MS-11106, Honda, MB 229.51, Mazda, Nissan, Suzuki, Toyota	

OEM analoglari

BMW

83212405950, 83212365929, 83212465854, 550050412, 89999011440, 550042690, 83212405099, 83212465856, 550042679

General Motors

88863191, 88863192, 88863193

Mercedes-Benz

A001989160111

To'xtatilgan qadoqlash

<i>Qadoqlash</i>	<i>Mahsulot kodi</i>	<i>Shtrix-kod</i>
4 L	1111137-004-01-A01	
20 L, ecobox	1111137-B20-01-888	
208 L	1111137-208-01-A01	
	1111137-208-01-888	