

RAVENOL RSE Racing Sport Ester 10W-50 poyga motor moyi

Yopishqoqlik: 10W-50

To'liq sintetik



1 L

Mahsulot kodi:

1141105-001

Mahsulot kodi:

1141105-001-01-999

Shtrix-kod:

4014835726819



4 L

Mahsulot kodi:

1141105-004

Mahsulot kodi:

1141105-004-01-999

Shtrix-kod:

4014835726895



5 L

Mahsulot kodi:

1141105-005

Mahsulot kodi:

1141105-005-01-999

Shtrix-kod:

4014835726857



10 L

Mahsulot kodi:

1141105-010

Mahsulot kodi:

1141105-010-01-999

Shtrix-kod:

4014835726840



20 L

Mahsulot kodi:

1141105-020



20 L, ecobox

Mahsulot kodi:

1141105-B20

Mahsulot kodi:

1141105-B20-01-888

Shtrix-kod:

4014835778429



60 L

Mahsulot kodi:

1141105-060



60 L, bosilgan barrel

Mahsulot kodi:

1141105-D60



208 L

Mahsulot kodi:
1141105-208



208 L, bosilgan barrel

Mahsulot kodi:
1141105-D28



1 000 L

Mahsulot kodi:
1141105-700

RAVENOL RSE Racing Sport Easter 10W-50 – to'liq sintetik, yuqori qo'shimchali, suyuq oqimli poyga motor moyi bo'lib, esterlar va polialfaolefinlar (PAO) aralashmasi asosida ishlab chiqilgan. Avtomobil poygalarida og'ir sharoitlarda qatnashadigan zamonaviy benzinli dvigatellar uchun mo'ljallangan.

Yuqori viskozite indeksi, siljishga nisbatan yaxshi chidamlilik va maxsus tanlangan volfram qo'shimchalari kompleksi tufayli RAVENOL RSE Racing Sport Easter 10W-50 sport rejimida ishlashda ajoyib natijalar ko'rsatadi.

Volfram xususiyatlari dvigatel ichki yuzasini silliqlab, ishqalanish va eskirishni kamaytiradi hamda mexanik samaradorlikni sezilarli darajada oshiradi, korroziya (oksidlanish) va ko'piklanishdan himoya qiladi.

Poyga motor moyi RAVENOL RSE SAE 10W-50 quyidagilarni ta'minlaydi:

- Ekstremal haydash sharoitlarida maksimal dvigatel quvvati
- Yuqori moy bosimi
- A'lo darajadagi korroziyadan himoya
- Past bug'lanish darajasi
- Atrof-muhitga ta'sirning kamayishi
- Katalizatorlarning tozaligi
- Ishqalanish yo'qotishlarini kamaytirish orqali yoqilg'i tejamkorligi
- A'lo darajadagi viskozite-harorat xususiyatlari
- Kamroq ko'piklanish
- Barqaror moy plyonkasi va yuqori eskirishdan himoya
- Qora shlam hosil bo'lishining oldini olish
- Qorindi va cho'kindilardan himoya

Xususiyatlari

Ism	Ma'nosi	Audit
Hamkorlar tomonidan testdan o'tkazilgan	Nürburgring	
Hamkorlar tomonidan tavsiya etilgan	Hockenheim Premium Partner, Ralf Shumaxer (Ralf Schumacher)	
Zichlik 20°C da	854 g/cm³	EN ISO 12185
Rang	Sariq-jigarrang	ingl
Viskozite 100°C da	17.5 mm²/s	DIN 51562-1
Viskozite 40°C da	111 mm²/s	DIN 51562-1
Viskozite indeksi VI	174	DIN ISO 2909
Yuqori haroratli viskozite (HTHS) 150°C da	5.3 mPa*s	ASTM D5481
Past haroratli viskozite (CCC) - 25°C da	4859 mPa*s	ASTM D5293
Past haroratda nasoslanish viskozitesi (MRV) -30°C da	15.000 mPa*s	ASTM D4684
Qotish harorati	-54 °C	DIN ISO 3016
NOACK bug'lanishi	6.1 %	ASTM D5800
Yong'in chiqish harorati	246 °C	DIN EN ISO 2592
Ishqoriy son	11.9 mgKOH/g	ASTM D2896
Sulfatli kul miqdori	1.3 %wt.	DIN 51575
Qo'llanish sohasi	Opel Motorsport	

OEM analoglari

Nissan

KLAM410520, KLAM410502, KLAM41050202, KLAM41052002, KLAM410504, KLAM41050204, KLAM41050402

To'xtatilgan qadoqlash

Qadoqlash	Mahsulot kodi	Shtrix-kod
1 L	1141105-001-01-100 1141105-001-06-999	4014835639218 2200000030412
10 L	1141105-010-01-999	
5 L	1141105-005-01-999	

<i>Qadoqlash</i>	<i>Mahsulot kodi</i>	<i>Shtrix-kod</i>
20 L	1141105-020-01-999	
20 L, ecobox	1141105-B20-01-888	
208 L	1141105-208-01-999	
60 L	1141105-060-01-999	