

4T qayiq dvigatellari uchun motor moyi - RAVENOL Outboardoil 4T 15W-40

Yopishqoqlik: 15W-40

Mineral



1 L

Mahsulot kodi:

1153205-001

Mahsulot kodi:

1153205-001-01-999

Shtrix-kod:

4014835729216



4 L

Mahsulot kodi:

1153205-004

Mahsulot kodi:

1153205-004-01-999

Shtrix-kod:

4014835729292



5 L

Mahsulot kodi:


1153205-005

Mahsulot kodi:

1153205-005-01-999

Shtrix-kod:

4014835729254



10 L

Mahsulot kodi:

1153205-010

Mahsulot kodi:

1153205-010-01-999

Shtrix-kod:

4014835729247



20 L

Mahsulot kodi:

1153205-020



20 L, ecobox

Mahsulot kodi:

1153205-B20

Mahsulot kodi:

1153205-B20-01-888

Shtrix-kod:

4014835780729



60 L

Mahsulot kodi:

1153205-060



208 L

Mahsulot kodi:

1153205-208

RAVENOL Outboardoil 4T SAE 15W-40 – mineral motor moyi bo'lib, NMMA FC-W talablari asosida in'yeksiya tizimiga ega 4 taktili tashqi qayiq dvigatellari uchun maxsus ishlab chiqilgan. Yuqori aylanish tezligi va yuklama sharoitida ham mukammal moylashni, kam kulli qo'shimchalar orqali ishqalanishga qarshi himoyani hamda korroziyadan himoyani ta'minlaydi. Ko'k rangga bo'yalgan.

NMMA FC-W sifat darajasidagi moy talab qilinadigan 4 taktili tashqi qayiq dvigatellarida qo'llaniladi, dengiz suvida ekspluatatsiya qilish uchun ham mos keladi.

Outboardoil 4T SAE 15W-40 quyidagilarni ta'minlaydi:

- Korroziyaga qarshi optimal himoya
- Yoqilg'i (shu jumladan etilsiz benzin) bilan aralashishga yaroqlilik
- Yuqori harorat va yuqori yuklamalarda ham barqaror moyli plyonka
- Zo'r ishqalanishga qarshi xususiyatlar
- Cho'kma hosil qilmasdan to'liq yonish
- Past darajadagi kokslash
- Ishqalanishga qarshi himoya

Xususiyatlari

Ism	Ma'nosi	Audit
Ishlab chiqaruvchi tomonidan ma'qullangan	NMMA FC-W, NMMA FB-83138K	
Mos keladi	Evinrude, Honda, Johnson, Mercury Verado, Nissan, Suzuki, Tohatsu, Yamaha	
Zichlik 20°C da	864 g/cm ³	EN ISO 12185
Rang	Ko'k	ingl
Viskozite 100°C da	14.4 mm ² /s	DIN 51562-1
Viskozite 40°C da	98.6 mm ² /s	DIN 51562-1
Viskozite indeksi VI	150	DIN ISO 2909
Qotish harorati	-33 °C	DIN ISO 3016
Yong'in chiqish harorati	236 °C	DIN EN ISO 2592
Ishqoriy son	7.5 mgKOH/g	ASTM D2896
Tavsiyalar	Evinrude, Honda, Johnson, Mercury Verado, Nissan, Suzuki, Tohatsu, Yamaha	
Dvigatelning taktligi	4T	

To'xtatilgan qadoqlash

Qadoqlash	Mahsulot kodi	Shtrix-kod
1 L	1153205-001-01-100	4014835634411 2200000020567
4 L	1153205-004-01-999	
5 L	1153205-005-01-100	4014835634459 2200000030597 2200000032478
10 L	1153205-010-01-999	
20 L	1153205-020-01-999	
60 L	1153205-060-01-999	
208 L	1153205-208-01-999	