

Mator moyi RAVENOL Motobike 4-T Ester 5W-40

Yopishqoqlik: 5W-40

To'liq sintetik



1 L

Mahsulot kodi:

1171102-001

Mahsulot kodi:

1171102-001-01-999

Shtrix-kod:

4014835730717



4 L

Mahsulot kodi:

1171102-004

Mahsulot kodi:

1171102-004-01-999

Shtrix-kod:

4014835730793



20 L

Mahsulot kodi:

1171102-020



20 L, ecobox

Mahsulot kodi:

1171102-B20



60 L

Mahsulot kodi:

1171102-060



208 L

Mahsulot kodi:

1171102-208

RAVENOL Motobike 4-T Ester SAE 5W-40 – bu 4 taktli mototsikl dvigatellari uchun maxsus ishlab chiqilgan zamonaviy sintetik motor moyidir. Yonilg'i tejamkorligini ta'minlaydi.

Mototsikl dvigatelini og'ir ekspluatatsiya sharoitlarida, jumladan uzoq muddatli yuqori aylanish tezligida ishonchli himoya qiladi. Quruq mufta va moyli vanna ichidagi muftali sport mototsikllarning to'rt taktli dvigatellari uchun maxsus ishlab chiqilgan.

RAVENOL Motobike 4-T Ester SAE 5W-40 — bu aynan motosport uchun yaratilgan yangi yuqori texnologiyali mahsulot hisoblanadi.

SAE 5W-40 viskozit sinfiga ega moy qo'llanilishi talab etiladigan barcha turdagi 4 taktli mototsikl dvigatellari uchun ishlatiladi.

Motobike 4-T Ester SAE 5W-40 quyidagilarni ta'minlaydi:

- Dvigatelning barcha muhim uzal va detallari uchun darhol yog'lanishni
- Moyning past sarfi tufayli kam pufaklanish
- Noqulay sharoitlarda ham shlam, nagar va korroziyadan himoya
- Turli haroratlarda gidroturkagichning uzluksiz va muammosiz ishlashi
- Yonish kameralarida, piston halqalari va klapanlar zonasida nagar hosil bo'lmasligi
- Moy almashtirish oralig'i davomida o'zgarmas viskozitani, yuqori viskozit indeks bilan
- Muhrlovchi materiallarga nisbatan neytral ta'sir

Xususiyatlari

Ism	Ma'nosi	Audit
API	SN	
JASO	MA2	
Mos keladi	Aprilia, BMW, Ducati, Honda, Kawasaki, Moto-Guzzi, Suzuki, Triumph, Yamaha	
Zichlik 20°C da	848 g/cm ³	EN ISO 12185
Rang	Och jigarrang	ingl
Viskozite 100°C da	13.7 mm ² /s	DIN 51562-1
Viskozite 40°C da	83 mm ² /s	DIN 51562-1
Viskozite indeksi VI	169	DIN ISO 2909
Past haroratli viskozite (CCS) - 30°C da	5937 mPa*s	ASTM D5293
Past haroratda nasoslanish viskozitesi (MRV) -35°C da	28.300 mPa*s	ASTM D4684
Qotish harorati	-39 °C	DIN ISO 3016
NOACK bug'lanishi	5.8 %	ASTM D5800
Yong'in chiqish harorati	244 °C	DIN EN ISO 2592
Ishqoriy son	7.6 mgKOH/g	ASTM D2896
Sulfatli kul miqdori	0.87 %wt.	DIN 51575
Dvigatelning taktligi	4T	
Tavsiyalar	Aprilia, BMW, Ducati, Honda, Kawasaki, Moto-Guzzi, Suzuki, Triumph, Yamaha	

OEM analoglari

Alpine

0121421, 0121422, 121422, 121421

BMW

83212365958, 07510037633, 83122153837, 83122153841, 83122158687, 83122405887, 83122405888, 83122405889, 83212455132, 83122405890, 83122406462, 83122406465, 83212444514, 83122406463, 83212410657, 83212410658

To'xtatilgan qadoqlash

Qadoqlash	Mahsulot kodi	Shtrix-kod
20 L	1171102-020-01-999	

<i>Qadoqlash</i>	<i>Mahsulot kodi</i>	<i>Shtrix-kod</i>
60 L	1171102-060-01-999	