

RAVENOL Hydraulikoel TS 100 (HLP) **gidravlik moyi**

Yopishqoqlik: 100**Mineral****1 L**

Mahsulot kodi:
1323107-001

**5 L**

Mahsulot kodi:
1323107-005
Mahsulot kodi:
1323107-005-01-999

**10 L**

Mahsulot kodi:
1323107-010
Mahsulot kodi:
1323107-010-01-999

**20 L**

Mahsulot kodi:
1323107-020
Mahsulot kodi:
1323107-020-01-999

**20 L, ecobox**

Mahsulot kodi:
1323107-B20

**60 L**

Mahsulot kodi:
1323107-060
Mahsulot kodi:
1323107-060-01-999

**208 L**

Mahsulot kodi:
1323107-208
Mahsulot kodi:
1323107-208-01-999

**1 000 L**

Mahsulot kodi:
1323107-700

Xususiyatlari

Ism	Ma'nosi	Audit
ASTM	D6158	
Talablarga mos keladi	AFNOR NFE 48-603 HM, Bosch Rexroth RE 90220, Cetop RP 91H HM, Danieli Hydraulics, FZG Test A 8,3/90, GB 111118.1 L-HM, ISO 11158 HM, Parker Denison HF-0, Parker Denison HF-1, Parker Denison HF-2, SAE MS 1004 HM, SEB 181.222, Sauer-Danfoss 520L0463, Swedish Standard 155434, VDMA 24318, Vickers Pumpentest	
Spetsifikatsiyalarga mos keladi	DIN 51524-2, ISO 6743-4 HM	
Zichlik 20°C da	875 g/cm ³	EN ISO 12185
Rang	Sariq	ingl
Viskozite 100°C da	11.2 mm ² /s	DIN 51562-1
Viskozite 40°C da	100.2 mm ² /s	DIN 51562-1
Viskozite indeksi VI	98	DIN ISO 2909
Qotish harorati	-21 °C	DIN ISO 3016
Yong'in chiqish harorati	264 °C	DIN EN ISO 2592
Tavsiyalar	AFNOR NFE 48-603 HM, ASTM D6158, Bosch Rexroth RE 90220, CETOP RP 91H HM, Danieli Hydraulics, FZG-Test A 8,3/90, GB 111118.1 L-HM (conventional), ISO 11158 HM, Parker Denison HF-0, Parker Denison HF-1, Parker Denison HF-2, SAE MS1004 HM, SEB 181.222, Sauer-Danfoss 520L0463, Swedish Standard SS 155434, VDMA 24318, Verwendung lt. Betriebsanleitung, Vickers-Pumpentest	
Viskozite indeksi	100	

To'xtatilgan qadoqlash

Qadoqlash	Mahsulot kodi	Shtrix-kod
1 L	1323107-001-06-999	