

# RAVENOL Vakuumpumpenoel ISO VG 46 vakuu moyi

**Yopishqoqlik: 46**

**Mineral**



**1 L**

Mahsulot kodi:  
**1330705-001**



**5 L**

Mahsulot kodi:  
**1330705-005**



**20 L**

Mahsulot kodi:  
**1330705-020**  
Mahsulot kodi:  
1330705-020-01-999  
Shtrix-kod:  
4014835758629



**20 L, ecobox**

Mahsulot kodi:  
**1330705-B20**



**60 L**

Mahsulot kodi:  
**1330705-060**



**208 L**

Mahsulot kodi:  
**1330705-208**

**RAVENOL Vakuumpumpenoil ISO VG 46** — bu yuqori unumdorlikka va tegishli sohalarda keng qo'llanilish imkoniyatiga ega optimal legirlangan mineral vakuum moyidir.

U yaxshi yopishqoqlik-harorat ko'rsatkichlari, qarishga nisbatan yuqori chidamlilik va ishonchli korroziyadan himoya bilan ajralib turadi. Maxsus tanlangan qo'shimchalar paketi og'ir yuklamalarda ham mukammal ishqalanishga qarshi himoyani ta'minlaydi. Muhrlovchi materiallarga nisbatan neytral hisoblanadi.

**RAVENOL Vakuumpumpenoil ISO VG 46** vakuum nasoslarini (plastinkali nasoslar, diffuzion nasoslar, turbonasoslar) moylash uchun qo'llaniladi, bunda mineral moydan foydalanish talab etiladi, shuningdek, karterni moylashda ham ishlatiladi.

**Vakuumpumpenoil ISO VG 46** qo'llanilishi quyidagilarni ta'minlaydi:

- Yuqori darajadagi ish samaradorligi
- A'lo darajadagi yopishqoqlik-harorat xususiyatlari
- Zo'r darajadagi ishqalanishga qarshi himoya
- Korroziyaga qarshi mukammal himoya
- Muhrlovchi materiallarga nisbatan neytral ta'sir

## Xususiyatlari

| Ism                                | Ma'nosi                                                                                                                                                                                                                               | Audit           |
|------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| Talablarga mos keladi              | Alcatel 100, Alcatel 119, Alcatel 120, BUSCH VM, BUSCH VMH, Balzers P3, Becker Vakuumpumpen, Beckmann 19, Fisherbrand 19, Hyvac 93055, Kinney Type A, Leybold-Heraeus 175, PVR Rotant, SAVANT SPO-1, Ulvac 100                        |                 |
| Spetsifikatsiyalarga mos keladi    | DIN 51506 VC, ISO 6743-3 DVA, ISO 6743-3 DVC                                                                                                                                                                                          |                 |
| Zichlik 20°C da                    | 854 g/cm <sup>3</sup>                                                                                                                                                                                                                 | EN ISO 12185    |
| Rang                               | Och sariq                                                                                                                                                                                                                             | ingl            |
| Viskozite 100°C da                 | 7.4 mm <sup>2</sup> /s                                                                                                                                                                                                                | DIN 51562-1     |
| Viskozite 40°C da                  | 47.2 mm <sup>2</sup> /s                                                                                                                                                                                                               | DIN 51562-1     |
| Viskozite indeksi VI               | 121                                                                                                                                                                                                                                   | DIN ISO 2909    |
| Qotish harorati                    | -36 °C                                                                                                                                                                                                                                | DIN ISO 3016    |
| Yong'in chiqish harorati           | 244 °C                                                                                                                                                                                                                                | DIN EN ISO 2592 |
| Uglerodli qoldiq (Konradson usuli) | 0.05 %                                                                                                                                                                                                                                | DIN 51551       |
| 0,01 bar bosimda qaynash harorati  | 112                                                                                                                                                                                                                                   | DIN 51757       |
| Qaynayotgan bug' bosimi            | 3 x 10 <sup>-3</sup> bar                                                                                                                                                                                                              | DIN 51757       |
| Tavsiyalar                         | Alcatel 100, Alcatel 119, Alcatel 120, BUSCH VM, BUSCH VMH, Balzers P3, Becker Vakuumpumpen, Beckmann 19, Edwards Ultragrade 19, Fisherbrand 19, Hyvac 93055, Kinney Type A, Leybold-Heraeus 175, PVR Rotant, SAVANT SPO-1, Ulvac 100 |                 |

## To'xtatilgan qadoqlash

| Qadoqlash | Mahsulot kodi      | Shtrix-kod |
|-----------|--------------------|------------|
| 5 L       | 1330705-005-01-999 |            |
| 60 L      | 1330705-060-01-999 |            |
| 208 L     | 1330705-208-01-999 |            |