

Suyuq surtma RAVENOL Mehrzweckfett m. MOS 2



1 kg

Mahsulot kodi:

1340103-001

Mahsulot kodi:

1340103-001-03-000

Shtrix-kod:

4014835200333



5 kg

Mahsulot kodi:

1340103-005

Mahsulot kodi:

1340103-005-03-000

Shtrix-kod:

4014835200357



10 kg

Mahsulot kodi:

1340103-010

Mahsulot kodi:

1340103-010-03-000

Shtrix-kod:

4014835200319



15 kg

Mahsulot kodi:

1340103-015



25 kg

Mahsulot kodi:

1340103-025

Mahsulot kodi:

1340103-025-03-000

Shtrix-kod:

4014835200326



100 g

Mahsulot kodi:

1340103-100

Mahsulot kodi:

1340103-100-04-999

Shtrix-kod:

4014835844452



180 kg

Mahsulot kodi:

1340103-180

Mahsulot kodi:

1340103-180-03-000

Shtrix-kod:

4014835200371



200 g

Mahsulot kodi:

1340103-200



400 g

Mahsulot kodi:

1340103-400

Mahsulot kodi:

1340103-400-04-999

Shtrix-kod:

4014835768246

RAVENOL Mehrzweckfett mit MoS2 — bu mineral asosli, litiyli sovun bilan qotirilgan, antioksidant va korroziyaga qarshi qo'shimchalar, shuningdek molibden disulfidi (MoS2) qo'shilgan avtomobil surkovchi moyidir.

Molibden disulfidining qo'shilishi **RAVENOL Mehrzweckfett mit MoS2** ni old g'ildirakli va to'liq g'ildirakli avtomobillarning bir xil burchak tezligidagi sharniyorlarini moylashda qo'llash imkonini beradi. Ushbu moy sho'r suvga nisbatan chidamli hisoblanadi.

Qo'llanilish sohasi:

RAVENOL Mehrzweckfett mit MoS2 texnik xizmat ko'rsatish vaqtida ko'pincha moylanmay qoladigan, yetib borish qiyin bo'lgan joylar va aylanuvchi uskunalarning detallari uchun moylash vositasi sifatida mo'ljallangan.

RAVENOL Mehrzweckfett mit MoS2 shassi qismlarini moylash uchun tavsiya etiladi.

Mehrzweckfett mit MoS2 qo'llanilishi quyidagilarni ta'minlaydi:

- A'lo darajadagi aşinaga qarshi himoya
- Juda yaxshi mexanik barqarorlik
- Korroziyaga qarshi mukammal himoya
- Metall yuzalarga yuqori yopishish xususiyati
- Oksidlanishga yuqori chidamlilik

Xususiyatlari

Ism	Ma'nosi	Audit
Spetsifikatsiyalarga mos keladi	DIN 51502 KPF2K-30, ISO 6743-9: ISO-L-XCCIB2	
Rang	Qora-kulrang	ingl
Qovushqoqlashtiruvchi modda	Litiyev sovun asosida	DIN 51757
Qo'shimchalar	molibden disulfidi	DIN 51757
NLGI-Class	2	DIN 51818
Mahsulotlar tasnifi	KPF2K-30	DIN 51502
Ish harorati	-30 / +120 °C	DIN 51825
Ish harorati (qisqa muddatli)	130 °C	DIN 51757
Penetratsiya, 60 aylanish	265-295	ISO 2137
Korroziyadan himoya testi, namlik kamerasi	1	DIN 51802
Tomchilash harorati	180 °C	DIN ISO 2176
Misga korroziya testi, 120°C/24 soat	1	DIN 51811
Suv o'tkazmaslik (3 soat/90°C)	1-90 °C	DIN 51807-1
VKA payvandlash yuklamasi	2800 - 3000 N	DIN 51350-4
Kinematik viskozite 40°C da	80 mm²/s	DIN 51562-1

OEM analoglari

Alpine

0101061, 0101065, 0101062, 0101063, 0101064, 0101066

BMW

83230417754

FEBI

02582, 02597, 2582, 2597

Ford

1720193, 1019761

Hyundai Motor

4959022B00A

Mercedes-Benz

A001989035112

Polaris

2871515, 2871551

SWAG

99830001

Volkswagen Group

G052723A2, G052172A2

Yamalube

ACCMOLDMGS10, ACCMOLDMGS05

To'xtatilgan qadoqlash

<i>Qadoqlash</i>	<i>Mahsulot kodi</i>	<i>Shtrix-kod</i>
15 kg	1340103-015-03-000	
200 g	1340103-200-04-999	
400 g	1340103-400-04-000	4014835200340 2200000040480